

record DFA 127

automatic drive system for swing doors



record DFA 127

FEATURES	BENEFITS
3 Models: Standard – Inverse - Fire	Provision for all standard options.
Compact	Less overhead space required for drive unit installation and less obtrusive.
Powerful	Doors to 250Kg and Size 6 Closer. Robust and reliable mechanics.
Gentle	Low energy mode for the most sensitive of installation requirements.
Safe	No emergency power required for deemed exits, simply use the Inverse model for fail open.
Fire	Fire approved model.
Flexible installation capabilities	Transom mount or Door mount, Hinged or Pivot installations.
Full power – Low energy	Suitable for all types of installations, including Aged Care and similar sensitive cases. (note: swing door operators are not recommended for high wind resistance installations.
Smoothness and quietness of operation	Near silent and so effortlessly opens and closes that it is almost inconspicuous in its presence.
European standard DIN18650 compliant worldwide	Testing authority is part of ILAC, internationally approved NATA partner, meets all Australian requirements.
Integrated sequential closing control	Ensures consistent sequential operation of double swing door installations.
Push and Go	Enables manual assist operation for fully able users and push button or magic switch open for disabled users, while preventing constant open from pedestrians walking past the door.
Automatic reverse	Prevents collision and enables retry in closing.
Electromagnetic brake	Ideal for room pressure systems to assist in keeping door closed.
BDED programming control panel	Enables simple mode change and programmability in one unit with LED error display.
Wide opening angle up to 115 degrees	Allows for clear door width access where building design allows for door to open past 90 degrees.